ZIGBEE REMOTE CONTROL OF ROBOT BASED ON EMBEDDED TECHNOLOGY

By

Maria Chaudhry

01-113092-013

Supervised by

Engr. Muneeb Yaqoob



2009-2013

A Report is submitted to the Department of Computer Science,

Bahria University, Islamabad.

In partial fulfillment of requirement for the degree of BS(ETM)

Abstract

Many developed countries are working on advancement, with keen focus on specialized products e.g implementation of complex algorithms etc. Designs that use simple algorithms and techniques to perfom complex tasks are the need of the day. Mobile robots have broad prospect of applications in remote control especially wireless. Continuous development of embedded technology and system provides good platform for mobile embedded system robots in hardware. With Zigbee radios of 802.15.4 protocol operating system, this project puts forward a kind of remote control method of mobile robots supporting long range, simple design and efficiency. The previous research experiments have proved that embedded mobile robot has low power consumption and strong real-time control for long range. This also proves the validity of this method in user specified tasks handling.

Table of Contents

CERTIFICATE
DEDICATION
ACKNOWLEDGMENT
ABSTRACT
TABLE OF CONTENTS
CHAPTER # 1
INTRODUCTION
1.1 PROJECT BACKGROUND
1.2 PROBLEM DESCRIPTION
1.3 PROJECT OBJECTIVES
1.4 HYPOTHESIS TO TEST
1.5 PROJECT SCOPE
1.5.1 SCOPE OF APPLICATION OF ZIGBEE
CHAPTER # 26
LITERATURE REVIEW6
CHAPTER # 3 12
REQUIREMENT SPECIFICATIONS 12
3.1 EXISTING SYSTEM
3.2 PROPOSED SYSTEM
3.2.1 ZIGBEE TECHNOLOGY
3.3 REQUIREMENT SPECIFICATION 14
3.3.1 MICROCONTROLLER

	3.3.4 XBEE PRO SERIES 1 MODULE	15
	3.3.5 LARGE OMNI DIRECTIONAL WHEELS	15
	3.3.6 POWER SUPPLY	15
	3.3.7 HARDWARE AND SOFTWARE USED	15
3	.4 USE CASES	16
	3.4.1 NETWORK NODES	16
	3.4.2 BUILT-IN LIBRARY	16
	3.4.3 ZIGBEE-MODEMS	
	3.4.4 ETRX1	17
	3.4.5 MODEM CONFIGURATION	17
C	HAPTER # 4	18
S	YSTEM DESIGN	18
4	1 SYSTEM ARCHITECTURE	19
4	2 DESIGN CONSTRAINTS	20
4	3 DESIGN METHODOLOGY	20
4	4 HARDWARE DESIGN COMPONENTS	21
	4.4.1 PIC 18F4520 MICROCONTROLLER	21
	4.4.2 CAPACITOR 10μF 16ν	22
	4.4.3 RESET SWITCH	23
	4.4.4 CAPACITOR CERAMIC	24
	4.4.5 OSCILLATOR 10MHz	25
	4.4.6 CROCODILE SWITCH	26
	4.4.7 3M IC HOLDER	27
	4.4.9 DIODE IN4001	29
	4.4.10 Regulator 7805	30
	4.4.11 REGULATOR 317	31
	4.4.12 TIP122	32
	4.4.13 TIP127	
	4.4.14 OPTOISOLATOR C109	34
	4.4.15 2N2222 NPN TRANSISTOR	100
	4.4.16 TIP 147	
	4.4.17 TIP 142	
	4.4.18 TERMINAL BLOCK	38
	4.4.19 1K RESISTOR	
	4.4.19 10K RESISTOR	
	4.4.20 XBEE BREAKOUT BOARD	
	4.4.21 XBEE EXPLORER USB	
	4.4.22 DC POWER SUPPLY	43

4.4.23 XBEE 802.15.4 RADIO	44
4.4.24 FUSE HOLDER	45
4.4.25 PICKIT 3	46
4.4.26 MINI USB CABLE	47
4.4.27 BUTTON SWITCH	48
4.4.28 JUMPER CABLES	
4.4.29 CRIMSHELL CONNECTOR	
4.4.30 BATTERY CHARGER	
4.4.31 8224 Brush DC Motor	
4.4.32 HEAT SINKER	
4.5 ASSEMBLY-LEVEL AND PART-LEVEL DRAWINGS	54
CHAPTER # 5	56
SYSTEM IMPLEMENTATION	56
5.1 SYSTEM INTEGRATION	57
5.2 PROCESSING LOGIC	59
5.2.1 Transmitter End Configuration	59
5.2.2 RECEIVER END CONFIGURATION	
5.3 DEVELOPMENT ENVIRONMENT	
5.3.1 C Programming	
5.3.2 X-CTU SOFTWARE	61
CHAPTER # 6	63
SYSTEM TESTING AND EVALUATION	63
6.1.1 ERROR ANALYZER	64
6.2 INSTALLATION TESTING	
6.2.1 NAVIGATION CONTROL	65
6.3 LOAD TESTING	65
6.4 SECURITY TESTING	65
CHAPTER # 7	66
CONCLUSION	66
APPENDICES	68
APPENDIX A	69
USER MANUAL	
APPENDIX B	76

REFERENCES	
LIST OF TABLES	
	1005H10,5 *10