

FINAL YEAR PROJECT REPORT

3D PRINTER

In fulfillment of the requirement For degree of BEE (Electronics)

By

MUHAMMAD SAAD QADEER MUHAMMAD ASIM WAJIH UL HASSAN 30993 BEE(ELECTRONICS) 31005 BEE(ELECTRONICS) 25476 BEE(ELECTRONICS)

SUPERVISED

BY

ENGR. TAIMOOR ZAFAR

BAHRIA UNIVERSITY (KARACHI CAMPUS) 2012-2016

ACKNOWLEDGEMENTS

We would like to thank everyone who had contributed to the successful completion of this project. We would like to express my gratitude to my research supervisor, Mr TAIMOOR ZAFAR for his invaluable advice, guidance and his enormous patience throughout the development of the research.

In addition, we would also like to express my gratitude to our loving parent and friends who had helped and given me encouragement.

3D PRINTER

ABSTRACT

3D printer is transforming the world by changing the way we produce objects. 3D printing is known as additive manufacturing process where objects are made layer by layer by adding plastic material (namely PLA). This process allows designers to create models at a very low cost. The printer is mainly designed for the purpose of prototyping. Initially a CAD model is designed on Auto Cad which is then converted in to G-Code. The G-Code is a language which is understandable by printer that tells the actuator part of the printer as to what function is to be performed. The Auto Cad generates .STL files which is converted in to G-Code using a software CURA. The machine can be operated using a smart LCD controller or by Host software between the PC and the printer that is pronterface which transmits the G-Code through universal serial bus (USB).

TABLE OF CONTENTS

DECLARATION	ii
APPROVAL FOR SUBMISSION	iii
ACKNOWLEDGEMENTS	vi
ABSTRACT	vii
TABLE OF CONTENTS	viii
LIST OF TABLES	xi
LIST OF FIGURES	xii
LIST OF SYMBOLS / ABBREVIATIONS	xiv
LIST OF APPENDICES	xv

CHAPTER

1	INTR	ODUCT	ION		
	1.1	Backg	round	16	
	1.2	Proble	m Statements	16	
	1.3	Aims	and Objectives	17	
	1.4	Scope	of Project	18	
2	LITE	RATUR	E REVIEW		
	2.1	Micro	controller ATmega 2560	19	
	2.2	Heat s	ensor	20	
	2.3	Limit	Limit switches		
	2.4	Heatin	Heating element		
	2.5	Mosfe	Mosfet		
	2.6	Resett	Resettable fuse		
	2.7	Steppe	Stepper motor driver		
	2.8	Nozzle	design	24	
		2.8.1	Cold end	24	
		2.8.2	Hot end	25	
		2.8.3	Integrated cold and hot end	26	
				viii	

2.9	Slicing software	28
2.10	Hosting software	29

DESI	GN AND I	METHODOLOGY	
3.1	Interfaci	ing circuitry	30
3.2	Circuits		33
	3.2.1	Motor circuit	33
	3.2.2	Thermistor heater and fan circuit	35
	3.2.3	Limit switch and LCD circuit	36
	3.2.4	Power supply	38
3.3	Ramps	1.4	39

IMPI	LMENTATION	
4.1	Mechanical frame	40
4.2	Movement along axes	41
4.3	Extruder	42
4.4	Printing bed	43
4.5	Procedure	44
4.6	Smart controller (LCD)	45

5 RESULTS AND DISCUSSIONS

3

4

5.1	Testin	Testing of stepper motors		
5.2	Problems			47
	5.2.1	Mechani	cal	48
		5.2.1.1	Motor selection	48
		5.2.1.2	Motor coupling	48
		5.2.1.3	Nozzle	48
	5.2.2	Electronic	S	48
		5.2.2.1	Stepper motor drive	48
		5.2.2.2	Wrath of wire	49
				ix

		5.2.2.3	Heating issues	49
	5.2.3	Software		49
		5.2.3.1	Interfacing software	49
		5.2.3.2	Software operation	49
	5.2.4	Printing		50
		5.2.4.1	Flow of material	50
		5.2.4.2	Sticking problems	50
5.3	Solutio	50		
	5.3.1	Mechanical		50
		5.3.1.1	Motor selection	50
		5.3.1.2	Motor coupling	51
		5.3.1.3	Nozzle	51
	5.3.2	Electronics		51
		5.3.2.1	Stepper motor driver	51
		5.3.2.2	Wrath of wire	51
		5.3.2.3	Heating issues	51
	5.3.3	Software		52
		5.3.3.1	Interfacing software	52
		5.3.3.2	Software operation	52
	5.3.4	Printing		52
		5.3.4.1	Flow of material	52
		5.3.4.2	Sticking problems	52
5.4	Final	output		53

6	CON	CONCLUSION AND RECOMMENDATIONS			
	6.1	Conclusion	56		
	6.2	Recommandations	56		
REFI	ERENCE	S	58		
APPI	ENDICES	5	59		
			,		